



TECHNICAL SPECIFICATION

FLOOR BOXES - CABLE MANAGEMENT



DESCRIPTION

RELITE Raised Floor boxes range is a unique, stylish and robust unit designed to give quick and simple solutions to raised access floor installations.

GENERAL FEATURE

- Overall dimensions 310 X 220 X 80mm.
- Panel cut out 300 x 200mm.
- Min plug space 28mm.
- Socket space 39mm.
- Reversible lid /trim assembly manufactured from flame retardant ABS.
- 2 cable exit flaps providing 60x15mm openings.
- Integral moulded lifting handle.
- 4 unique relocatable spring fixing clips for quick fit.
- Both 3 and 5 compartment formats fit within a common panel cut out.
- Can be used with raised floor system or for conduit entry.
- Single compartment box also available.
- Floor box for installation in screed.
- Floor box with additional space above or below plates.
- Shallow floor boxes
- Special finishes
- Full Pre-wiring options available
- Other special requirements may be available.



LID TRAY ASSEMBLY

The carpet trim and lid tray are moulded from flame retardant ABS, with both having a steel reinforced section to ensure maximum rigidity. Each lid is providing with two cable outlet brackets that are securely fixed into the lid tray, together with a moulded integral lid handle. The carpet trim and lid tray can be rotated through 180° to allow the lid to be opened in either direction. Available space above plates with lid closed is 28mm and the standard colour of the moulding is dark grey.

BOX BASE

The Box base is manufactured from galvanised steel and is provided with 20 and 25mm knockouts on all four sides. Dividing fillets are providing to separate the internal services. To ensure maximum security for the electrical services, the accessory plate fixing screws are located in an inaccessible position. Available space under accessory plates are 39mm.

MODEL

DESCRIPTION

RL -

Raised Floor Box - 310 x 220 x 80mm