

ML

ML 160W E27 220-230V SG 1CT/24

Mixed Light lamps

Product data

• General Information

Cap-Base E27 [E27]
Bulb Shape F75 [E 75mm]
Operating Position VBU/VBD30 [Vertical or Base Up/Base Down +/-30D]
Life To 5% Failures (Nom)
Life To 20% Failures (Nom)
Life To 50% Failures (Nom)
Life To 50% Failures (Nom)

• Light Technical

2850 lm
3150 lm
82 %
87 %
78 %
83 %
399
380
3600 K
19 lm/W
63

• Operating and Electrical

Lamp supply voltage Power (Rated) (Nom)	220-230 V 165.0 W	
Lamp Current (EM)	0.8 A	
(Max) Lamp Current (EM)	0.72 A	
(Min) Lamp Current (EM)	0.76 A	
(Nom)		
Ignition Supply Voltage (Max)	170 V	
Voltage (Nom)	225 V	

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Bulb Finish Coated glass
Bulb Material Soft Glass

• Approval and Application

Energy Efficiency C
Label (EEL)
Mercury (Hg) 12 mg
Content (Nom)
Energy Consumption kWh/1000 h



• Luminaire Design Requirements

Bulb Temperature 350 °C (Max)

Cap-Base Tempera-200 °C

ture (Max)

• Product Data

Full product code 692059024694430

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and

Order product name EAN/UPC - Product ML 160W E27 220-230V SG 1CT/24


6920590246944 928601008902 Order code

Numerator - Quantity Per Pack Numerator - Packs 24

per outer box Material Nr. (12NC) 928601008902 Net Weight (Piece) 0.082 kg

remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing




ML 160W E27 220-230V SG

Product	D	C
ML 160W E27 220-230V SG 1CT/24	76 mm	172 mm



Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.