

LED WATERPROOF FITTING



Product Features

High Quality LED Tube, Anti UV and Flame retardance, Lamp Base equipped with wire protective rings and water proof glands, Sealing Clips - Plastic Clips, Lead wire Size - H05RNF3 x 1.5mm

Application

Car Park Lighting
Ware houses & Storage
Electrical & Plumbing Rooms
Body Work shops,
Garages, Factory

Advantages

80% Energy Saving
Environmentally Safe
Less Heat produced
Zero UV Emission
100% Poly Carbonate body
for non-breakage & durability



LED WATERPROOF FITTING

TECHNICAL DATA

Product Code	LEDRXWP111	LEDRXWP211	LEDRXWP122	LEDRXWP222
Power	1X11W	2X11W	1X22W	2X22W
Voltage	220-240V AC	220-240V AC	220-240V AC	220-240V AC
Luminous Flux*	1000 Lm	2000 Lm	2000 Lm	4000 Lm
Efficacy	100 Lm/W	100 Lm/W	100 Lm/W	100 Lm/W
Energy efficiency	A+	A+	A+	A+
Net weight	0.83 Kg	1.22 Kg	1.64 Kg	2.28 Kg
CRI	> 80	> 80	> 80	> 80
Beam angle	220°	220°	220°	220°
Operating temperature	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C	-20 °C to+40 °C
Storage temperature	Up to 50°C	Up to 50°C	Up to 50°C	Up to 50°C
Body Material	Poly Carbonate	Poly Carbonate	Poly Carbonate	Poly Carbonate
CCT	3000K / 6500K	3000K / 6500K	3000K / 6500K	3000K / 6500K
IP	65	65	65	65
Dimmable	No	No	No	No
Life Time	30,000Hrs	30,000Hrs	30,000Hrs	30,000Hrs
Cover	Clear Cover	Clear Cover	Clear Cover	Clear Cover
Finishing color	Grey	Grey	Grey	Grey
Mounting	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging	Surface/ Hanging
Size in mm (LXWXH)	650X80X86	650X120X85	1265X80X86	1265X120X85

*Lumen may change subject to lamp wattage

