



# **SOLID COPPER GROUNDING RODS**

## INTERNALLY THREADED

HEX solid Copper earth rods are made from 99.9% pure electrolytic copper. Solid Copper rods offers greater resistance to corrosion. They are ideally used in applications where soil conditions are very aggressive, for eg. soil with high salt content.

Rod Dia.	Length	Product Code
15 mm	1200 mm or 4'	HSC - 512
15 mm	1500 mm or 5'	HSC - 515
16 mm	1200 mm or 4'	HSC - 1612
20 mm	1200 mm or 4'	HSC - 520
20 mm	1500 mm or 5'	HSC - 521
20 mm	3050 mm or 10'	HSC - 1021

\* Tested as per UL 467 Standard.

\*\* Tested as per BS EN 62561 - 2 : 2012

## ACCESSORIES

Size	Item	Product Code
15 mm	Driving Head	HDH - 15
20 mm	Driving Head	HDH - 20
15 mm	Coupling Dowel	HCH - 15
20 mm	Coupling Dowel	HCH - 20
15 mm	Driving Tip	HDT - 15
20 mm	Driving Tip	HDT - 20

## EXTERNALLY THREADED

Dimensions Rod Size (Dia X Length)	Thread Dia. 'T'	Product Code
14 x 1200 mm	14	HBRS - 1412
14 x 1500 mm	14	HBRS - 1415
5/8" x 4"or 16 mm x 1200 mm	5/8"	HBRS - 112
5/8" x 5"or 16 mm x 1500 mm	5/8"	HBRS - 115
3/4" x 4'or 19 mm x 1200 mm	3/4"	HBRS - 212
3/4" x 5'or 19 mm x 1500 mm	3/4"	HBRS - 215

- Same accessories of copper bonded grounding rods are applicable.
- HEX also offers other sizes as per customer specification.